

## SYSTEM DESCRIPTION

Leveraging proprietary technology, the **EZ-RO 375/30ATM** system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 375 gal/day (1,419 L/day)\* and includes a 30-gallon (113.6 L) atmospheric tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements<sup>†</sup>.

## APPLICATIONS

Combi ovens

Steamers

Proofers

## FEATURES • BENEFITS

Meets combi oven and steamer equipment water quality standards; AÉÍ ö È á' YÉÉŋ s%áúú çás; Ýs%á %çç' corrosion problems due to high TDS, water hardness\*, and chlorides<sup>†</sup>

4CM cartridge provides optimal mineral content for proper function of conductivity sensors on steam equipment

Sealed atmospheric storage tank provides compact capacity and electronic pump delivers optimized water to downstream equipment

Pressure gauge allows monitoring of RO ÆÁ á×ú Ýáú %çç×ú Áú Úsí Èçŋ È

Built-in bypass, sample port and áÝ' ö%ç; ÝÝ×; | ç á× ÆÝá%çç È %çç' cartridge replacement

ZÚ ×úŋ áúú5ŋú çúÈ; ;: Áúúá È' Ç; çŋö'°; šáŋ; Áúŋ È' ŋŋáÝ±Ú ö á' í' ö' ò%çá; Úŋŋ È á' | Áú ÚÇ; çŋá' %çç%ç' decrease product life. Also can reduce sediment and chlorine to help protect the RO membrane\*

ŋŋ' | í' ö' ;' | í' Ý; í' ×áçŋ | ç' ö%çá Ú line to equipment

Installation kit comes complete with áŋŋŋ±' áŋŋ±Ý %ççÇ í áÈáŋŋ±' %ççö%çá' for installation

ŋŋ' | ; ŋŋ Èsú] P Ç; Ç ŋŋç; Ý%çá Ýá×' to two times more water than standard RO membranes<sup>†</sup>

Numerous patents pending on technology and other aspects of the product design

## INSTALLATION TIPS

Kí á×; Úí Ú ççç; á' Ýá; çí Ús; Úŋ | ç ŋŋK' 5

<sup>†</sup> When installed, serviced and maintained according to Pentair Everpure Installation Operation Instructions.

<sup>†</sup> Up to 50% recovery compared to standard ] P Ýúá; Ç Ýöŋ' | Ú sí ö; Úú

+Z' +Ýá' ;E

Feed water connection to system—should be COLD only. Tempered water up to 80°F " šççŋ' áÝ; ç'

' í Èí á; ús; | ç Ýúá; Ç Ý



United States |