


EZ-RO 650/30ATM wall mount

EZ-RO 650/30ATM with optional tank



30-gallon atmospheric tank

Leveraging proprietary technology, the **EZ-RO 650/30ATM** system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 650 gal/day (2,460 L/day)* and includes a 30-gallon (113.6 L) atmospheric tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements[†].

Combi ovens

Steamers

Proofers

Meets combi oven and steamer equipment water quality standards;

corrosion problems due to high TDS, water hardness*, and chlorides[†]

7CM cartridge provides optimal mineral content for proper function of conductivity sensors on steam equipment

Sealed atmospheric storage tank provides compact capacity and electronic pump delivers optimized water to downstream equipment

Pressure gauge allows monitoring of RO

Built-in bypass, sample port and cartridge replacement

decrease product life. Also can reduce sediment and chlorine to help protect the RO membrane*

line to equipment

Installation kit comes complete with

For use with steam generation only. Do not use for condensate or wash water.


cartridge removal and replacement.

Detailed, illustrated installation guide is included with each system.

[†] When installed, serviced and maintained according to Pentair Everpure Installation Operation Instructions.

[‡] Up to 50% recovery compared to standard RO systems with 25% recovery. EPA Est. 002623-IL-003

temperature and pressure. Provide a dedicated feed water supply



(57.9 cm x 44.2 cm x 20.3 cm)	81.0 lbs (36.8 kgs)
(74.7 cm x 47.0 cm x 65 cm) 30 gallons (113.6)	Grounded 115 VAC, 2 Amp
included	Up to 650 gpd (2,460 Lpd)*
	pressure*; production will vary based on water supply temperature and pressure
	Dependent on water level up to 3.25 gpm (12.3 L) @ 50 psi (3.4 bar)



For Pentair Everpure Product Warranties visit:
<http://pentair.com/assets/foodservice-warranty>

For Pentair Patent Information visit:
<http://pentair.com/patents>

United States | J a U | A U P | 9% | o U Z % A ; E ' | ' ' | ' g ' P E A U ' | J % | ' s Y | o U k a U | x | E a P U S I C | ' i f c Y | U S | x | E a P U S I C
 Australia | ' ' | J I E % ' ' U P | ' ' % C | E I E ± ' | a a ' p S ' | ' ' ' a Y a U % ' ' | ' ' | ' d | A | % | o U k a U | x | E a P U S I C
 China | ' ' 5 " A a c ' Z A % % K P ' | ' ' ' % ± ' % ' | ' ' China | ' ' | ' d | A | s ' E % % % U | x | E a P U S I C
 India | ' | a A o % C ! | ' ' a ' 5 A I U d i o U | ' | s a U | ' | K I % ' | ' ' | ' d | A | E C P % a Y a C | U | x | E a P U S I C
 Europe | ' Z | E a P U q % U | ' A P C | p | ' ; E c a Y a U | x | A q | A Y a | d | ' | A I C Y a % C | ' | ' 9 | U E a P U | ' | A P C | ' ' | ' d | A | Y % Y | o U k a U | a U | x | s I C
 Japan | ' C % % ; E s | ' 9 % ' C I a J K I A ± ' 5 | ' ' 9 % ' C I a J P U A a ' % % C | ' 1 % Y ' | ' | ' D % % % % | ' ' C % % C | ' ' | ' d | A | E I | o U k a U s I A
 Southeast Asia | ' ' 9 % A s A] I % | ' ' | ' D E ± Y ' | E a U | ' ' E ± % d U ' | ' ' | ' d | A | s Y | o U k a U | x | E a P U S I C

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.