

PLM SERIES FILTER SYSTEMS

The System:2 Mod Media PLM Series Aboveground System

Dimensions and Performance

EASYCLEAN™ D.E. FILTER SYSTEMS

D.E. Filter System comes in a variety of sizes to suit most

Ordering Information

| Product | Pump THP | Pump Cord | Hose Kit |
|---------|----------|-----------|----------|
| | | | |
| | | | |
| | | | |

¹

² Flow Rate and Turnover Capacity based on Filter.

³ WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

Dimensions and Performance

OptiFlo Pump



See page 353 for replacement parts.

SAND DOLLAR® FILTER SYSTEMS




Sand Dollar Filter System²

Our blow-molded process creates a one piece, non-corrosive tank of outstanding strength

provides excellent performance.

Featured Highlights

- Six-position 1-1/2 in. multiport valve
- New 1.0 THP OptiFlo® Pump
- One piece, durable non-corrosive tank
- Combination water and sand drain makes servicing and winterizing fast and easy
- Unionized Pump to Filter connection



Ordering Information

| Product | Pump THP | Pump Cord | Hose Kit (Ft.) | Effective Filtration Area (Sq. Ft.) | Flow ¹ Rate (GPM) | Turnover Capacity (In Gallons) ¹ | | | Tank Diameter (In.) | Tank Height (In.) | Sand Required (Lbs.) |
|-----------------------------------|----------|--------------------------|----------------|-------------------------------------|------------------------------|---|---------|---------|---------------------|-------------------|----------------------|
| | | | | | | 8 Hour | 10 Hour | 12 Hour | | | |
| SAND DOLLAR FILTER SYSTEMS | | | | | | | | | | | |
| PNSD0035OE1160 | 1.0 | Standard plug 3 ft cord | 6 ft | 1.4 | 35 | 16,800 | 21,000 | 25,200 | 16 | 28-1/2 | 100 |
| PNSD0035OE11X0 | 1.0 | Standard plug 3 ft cord | None | 1.4 | 35 | 16,800 | 21,000 | 25,200 | 19 | 34 | 150 |
| PNSD0040OE1162 | 1.0 | Standard plug 3 ft cord | 6 ft | 1.8 | 40 | 19,200 | 24,000 | 28,800 | 19 | 34 | 150 |
| PNSD0040OE11X0 | 1.0 | Standard plug 3 ft cord | None | 1.8 | 40 | 19,200 | 24,000 | 28,800 | 19 | 34 | 150 |
| PNSD0040OE1260 | 1.0 | Twistlock plug 3 ft cord | 6 ft | 1.8 | 40 | 19,200 | 24,000 | 28,800 | 19 | 34 | 150 |
| PNSD0060OE1160 | 1.0 | Standard plug 3 ft cord | 6 ft | 2.3 | 60 | 28,800 | 36,000 | 43,200 | 22 | 35-1/2 | 250 |
| PNSD0060OE11X0 | 1.0 | Standard plug 3 ft cord | None | 2.3 | 60 | 28,800 | 36,000 | 43,200 | 22 | 35-1/2 | 250 |
| PNSD0060OE1260 | 1.0 | Twistlock plug 3 ft cord | 6 ft | 2.3 | 60 | 28,800 | 36,000 | 43,200 | 22 | 35-1/2 | 250 |

¹ Flow Rate and Turnover Capacity based on Filter.

² WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

Dimensions and Performance



See pages 355 for replacement parts.

Featured Highlights

- for performance.
- One-piece polyethylene tank
- Multi-port valve selector activates backwashing action with one quick turn
- Easy-to-read top-mounted pressure gauge

installation and servicing

large capacity OptiFlo Series pump. Low maintenance

